

MC93ex-NI Mobile Computer

Accessories





Accessories for use in hazardous areas

Accessories are approved for:

- ATEX: Zone 2/22 (EPS 19 ATEX 1 239 X)
- IECEx: Zone 2/22 (IECEx EPS 19.0108X)
- NEC: Class I, II, III Div 2 (UL E321557)



Battery

Description	– Lithium polymer battery 3.6 V/7000 mAh(25.4Wh)
	- Hot-swappable
	May only be changed and charged outside hazardous areas!
Order no.	B7-A2Z0-0059



Spare keypad

	th MC93 ^{ex} -NI
May only be assemble/disass	semble outside
hazardous areas!	
with 29 keys, numeric	B7-A2Z0-0063
with 43 keys, numeric	B7-A2Z0-0065
with 53 keys, alphanumeric	B7-A2Z0-0066
with 53 keys, alphanumeric, VT-Emulation	B7-A2Z0-0067
	with 43 keys, numeric with 53 keys, alphanumeric with 53 keys, alphanumeric,



Stylus

Description	– Suitable for MC93 ^{ex} -NI
	– passive stylus
	- with spiral cable
	-3 pieces
Order no.	17-S1Z0-0008





Leather carry case

Description	- Certified in combination with MC93 ^{ex} -NI
	- With shoulder strap
	– Robust industry quality leather
	- Holder for stylus
	– Must be removed before inserting into Base station/Charging adapter
Order no.	B7-A2Z0-0060



Hand strap

Description	-1 piece
	- Color: black
Order no.	B7-A2Z0-0071



Screen protector

Order no.	B7-A2Z0-0061
	Must be applied and removed only outside hazardous areas!
	-5 pieces
Description	– Certified in combination with MC93 ^{ex} -NI





Passive device holder

Beschreibung	– Suitable for MC93 ^{ex} -NI – Suitable for mounting onto vehicles
	and fixed structures
	- Safe to use in hazardous areas
	– Attach onto a Pedestal Mount
	– Size (H x W x D): 120 x 104 x 53 mm
	– Weight: 294 g
	- Color: black
Bestellnummer	B7-A2Z0-0096
Bestellnummer	B7-A2Z0-0096



Accessories for use outside hazardous areas



4-slot battery charging station

Description	- Charging four batteries
	- Supports fast charging of the battery (charges from 0-90 % in about 3.5 hours)
Scope of delivery	4-slot battery charging station
Also required	(not included in the delivery)
	 Power supply with DC connecting cable (G7-A0Z0-0023)
	-AC power cable
Order no.	G7-A0Z0-0042



16-slot battery charging station

- Charging 16 batteries
 Supports fast charging of the battery (charges from 0-90 % in about 3.5 hours)
16-slot battery charging station
(not included in the delivery)
Power supply with DC connecting cable (G7-A0Z0-0045)
- AC power cable
GZ-A0Z0-0049



Base station

Dase station	
Description	- Charging the Mobile Computer (without Leather carry case)
	– Charging an additional battery
	- Communication via USB
	 Supports fast charging of the Mobile Computer and battery (charges battery from 0-90 % in about 3.5 hours)
	– LED notification of battery charging status
Scope of delivery	Base station
Also required	(not included in the delivery)
	 Power supply with DC connecting cable (G7-A0Z0-0023)
	-AC power cable
Order no.	G7-A0Z0-0041





Charging adapter for older Docking stations

Description	 Charge adapter for backward compatibility with MC9x Docking Station
	 Allows MC93^{ex}-NI (without Leather carry case) to be used with MC90/MC91/MC92 Docking Stations and 4-Slot Docking Stations
	Adapter does not provide communications support!
	 Adapter does not support fast charging of MC93^{ex}-NI
Scope of delivery	Charging adapter
Order no.	G7-A0Z0-0043



4-slot Ethernet base station

Description	– Will charge up to four MC93ex-NI
	- Allows network speeds up to 1 GB
	 Provides Ethernet daisy chaining support for connecting multiple base stations together.
	 Supports fast charging of the Mobile Computer (charges battery from 0-90 % in about 3.5 hours)
Scope of delivery	4-slot Ethernet base station
Also required	(not included in the delivery)
	 Power supply with DC connecting cable (G7-A0Z0-0045)
	,
Order no.	(G7-A0Z0-0045)





Power supply with DC connecting cable

Description	– for 4-slot battery charging station and Base station	
	– Input voltage: AC 100 bis 240 V	
	- Output voltage: DC 12 V/4.16 A/50 W	
Order no.	G7-A0Z0-0023	



Power supply with DC connecting cable

Description	– for 4-slot Ethernet base station	
	– Input voltage: AC 100 bis 240 V	
	– Output voltage: DC 12 V/9 A/180 W	
Order no.	G7-A0Z0-0045	



AC power cable

Description	-3-wire -country-specific	
Order no.	Version: US + Canada	G7-A0Z0-0024
	Version: EU + APAC	G7-A0Z0-0026
	(with plug IEC-60320-C13	Other country specific cables (with plug IEC-60320-C13) may be purchased from third-party suppliers.